

ASTM CATEGORY 1 : road only
Recommended weight limit : 120kg
Recommended tire sizes: 25 to 32 mm
Max. Pressure: 23mm 8.7 bars - 125 psi, 25/28mm 7.7 bars - 110 psi

REFERENCES WHEELS

R78701	Aksium RS SMU Rr M11	R99521	Aksium RS Rr
--------	----------------------	--------	--------------

RIMS

VALVE HOLE Ø (MM): 6,5 :

1	LV2403000	KIT FRONT/REAR RIM AKSIUM
---	-----------	---------------------------

SPOKES



2	LV2272700	KIT 10 FT/NDS AKSIUM RND SPK 283mm (OEM only)
3	L10845000	KIT 10 DS AKSIUM STEEL AERO SPOKES 299mm

HUB SHELLS

5	LM4066000	REAR HUB 608+6001 BEARINGS
6	L30871100	FTS-L ROAD FREEWHEEL BODY HG11 8/9 compatible
7	L30871200	FTS-L ROAD FREEWHEEL BODY ED11 8/9 compatible
8	LM4006700	INTERNAL FREEWHEEL SPACER FTSL/FTSX
9	L99500000	FTSL/FTSX FREEHUB BODY SEAL
10	L99603800	SHORT EXPENSIBLE BEARING SUPPORTS > 2008
11	L99603900	REAR AXLE QRM ROAD 2008
12	LM4057800	FTSL PAWLS KIT (ROAD WHEELS)

MAVIC Aksium RS

DELIVERED WITH

BR101 quick releases (M40350 firt, M40351 rear road, M40352 rear MTB) 1	
BR101 quick releases (M40350 firt, M40351 rear road, M40352 rear MTB) 1	
Rim tape	
Rim tape	
User guide	
User guide	

COMPATIBILITY

Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Freewheel: Shimano/Sram, convertible to Campagnolo with optional driver body	
Front axle: Quick Release only	
Front axle: Quick Release only	
Rear axle: Quick Release only	
Rear axle: Quick Release only	

Specifications

RIMS

- **Material** : S6000 Aluminum
- **Material** : S6000 Aluminum
- **Height** : 21 mm
- **Height** : 21 mm
- **Joint** : pinned
- **Joint** : pinned
- **Drilling** : traditional with H2 reinforcement
- **Drilling** : traditional with H2 reinforcement
- **Brake track** : UB Control
- **Brake track** : UB Control
- **Valve hole diameter** : 6.5 mm
- **Valve hole diameter** : 6.5 mm
- **Tire** : clincher
- **Tire** : clincher
- **Internal width** : 15mm
- **Internal width** : 15mm
- **ETRTO size** : 622x15C
- **ETRTO size** : 622x15C

SPOKES

- **Material** : steel
- **Material** : steel
- **Shape** : straight pull, round
- **Shape** : straight pull, round
- **Nipples** : steel, ABS
- **Nipples** : brass, ABS
- **Count** : 20 front and rear
- **Count** : 20 front and rear
- **Lacing** : radial front and rear non-drive side, crossed 2 rear drive side
- **Lacing** : radial front and rear non-drive side, crossed 2 rear drive side

WHEEL HUB

- **Front and rear bodies** : aluminum
- **Front and rear bodies** : aluminum
- **Axle material** : steel
- **Axle material** : steel
- Sealed cartridge bearings
- Sealed cartridge bearings
- **Freewheel** : FTS-L steel
- **Freewheel** : FTS-L steel

VERSIONS

- **Color** : Black only
- **Color** : Black only

WHEEL WEIGHTS

Wheel weight 1015